

CorePro LED PLC

CorePro LED PLC 9W 840 4P G24q-3

The Philips CorePro LED PLC integrates a LED light source into a traditional fluorescent form factor. This product is the ideal solution for uplamping in general lighting applications: it meets basic lighting requirements, offers significant energy savings, and is environmentally friendly.

Product data

• General Information

Cap-Base G24Q-3 [G24q-3] Main Application Industrial 30000 h Nominal Lifetime (Nom) Switching Cycle 50000X B50L70 30000

• Light Technical

Color Code 840 [CCT of 4000K (841)] Beam Angle (Nom) 120 950 lm Luminous Flux (Nom) Luminous Flux 950 lm (Rated) (Nom) 120° Rated Beam Angle 4000 K Correlated Color Temperature (Nom) Color Consistency <6 Color Rendering 83 Index (Nom) LLMF At End Of 70 % Nominal Lifetime (Nom)

• Operating and Electrical

Input Frequency 30000-80000 Hz 9 W Power (Rated) (Nom) Starting Time (Max) Warm Up Time To 0.5 sinstant full light 60% Light (Nom) Power Factor (Min) 8.0 Voltage (Nom) 20-50 V

• Temperature

35 °C T-Ambient (Max) T-Ambient (Min) -20 °C 65 °C T-Storage (Max) T-Storage (Min) -40 °C 75 °C T-Case Maximum (Nom)

· Controls and Dimming

Dimmable No

• Mechanical and Housing

Product Length 100 mm

• Approval and Application

Energy Saving Yes Product Suitable For Accent No Lighting Energy Efficiency Label (EEL)

Approval Marks

CE marking RoHS compliance

KEMA Keur certificate 12 kWh

Energy Consumption

kWh/1000 h

• Product Data

871869654117300 Full product code CorePro LED PLC 9W 840 4P Order product name G24q-3



CorePro LED PLC

EAN/UPC - Product Order code

8718696541173

Numerator - Quantity Per Pack

929001200902

per outer box Material Nr. (12NC)


Numerator - Packs 10

929001200902 Net Weight (Piece) 0.088 kg

Warnings and Safety


• NOTES: The overall energy efficiency and light distribution of any installation that uses these lamps are determined by the design of the installation.

Dimensional drawing




LEDtube PLC 9W G24q-3/840 4P

Product	D1	D2	A1	A2	A3
CorePro LED PLC 9W 840 4P G24q-3	24.3 mm	28.4 mm	128.3 mm	147.5 mm	163.1 mm



Photometric data





© 2016 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.